
## CAD-COLOR® SUPERTEK™ SUBLISTOP 2.0



### PRINTABLE, DYE-BLOCKING POLYURETHANE FILM

The first ever subli block material offering four way stretch! Utilising the patented STiX<sup>2TM</sup> charcoal-based adhesive. Applied quickly at low temperatures to eliminate heat press marks. Has a lightweight feel on the garment, with a soft touch. Will adhere to virtually all fabrics.



#### **AVAILABLE IN**

50 cm x 25 m rolls

#### RECOMMENDED FABRICS

- 100% Cotton
- 100% Polyester\*
- Polyester-cotton blends
- Lycra® / spandex blends
- Most nylon garments\*
- \* Test before application!

#### **CUTTING NOTES**

You should always test cut prior to any production run. Remember cutter settings will need to be adjusted as your blade ages. Cutting too deep will result in weeding or printing difficulties.

# CARE INSTRUCTIONS

Machine wash up to 40° C using mild detergent. Do not use bleach. Do not dry clean. Iron only inside out.

#### **STORAGE**

Store in cool, dry area. Avoid direct heat, sunlight and humidity.

#### **DETAILS**



#### APPLICATION INSTRUCTIONS

Temperature: 150° C

Time: 5 sec. Pressure: Medium

(#4-6 on Hotronix®)

Peel: Warm

Repress: 5 sec.

#### ACCESSORIES RECOMMENDED

- CAD-COLOR® MagicMask® High Tack
- **Grip Cover Sheet**
- Coversheet Non-Sticky
- EZ Weeder®, LED Weeder, LED Pin or Tweezers
- Squeegee

#### **KEY**



Easy weed



Ironable



Ironable only



Washable



Sublimation



Stretchable



Flock





Sticky carrier



Multi-color application



Peel hot



Application



Pressure

