



DURABLE SILICONE MATERIAL WITH A MATTE FINISH AND A SOFT TOUCH.

Silicone 500

It has a more matte finish, soft touch and is extremely durable. Fashion wear is enhanced by its unique 3D appearance. The material is a natural blocker, and is therefore suitable for sublimated polyester.



AVAILABLE IN

50 cm x 25 m rolls

RECOMMENDED FABRICS

- 100% Cotton
- 100% Polyester*
- Polyester-cotton blends
- Sublimated polyester

* Test before application!

CUTTING NOTES

You should always test cut prior to any production run. Remember cutter settings will need to be adjusted as the blade ages. For optimal cutting and weeding, maintain a line thickness of at least 2.5mm for lettering and logos.

APPLICATION INSTRUCTIONS

Silicon 500

- Temperature: 150°C
- Time: 20 sec.
- Pressure: Medium
- (#4-6 on Hotronix®)
- Peel: Cold
- Reprint: 5 sec.

MULTI-COLOR DESIGNS

CAD-CUT® Silicone is not suitable for multi-layer applications.

ACCESSORIES RECOMMENDED

- Grip Cover Sheet
- Cover Sheet - Non-Sticky
- EZ Weeder®, LED Weeder. LED Pin or Tweezers

CARE INSTRUCTIONS

Machine wash up to 60° C using mild detergent. Do not use bleach. Do not dry clean. Iron only inside out.

STORAGE

Store in cool, dry area. Avoid direct heat, sunlight and humidity.


DETAILS



KEY

Easy weed	Thin
Ironable	Sticky carrier
Ironable only inside out	Multi-color application
Washable	Peel hot
Sublimation	Application
Stretchable	Pressure
Flock	


CAD-CUT® SILICONE 500



001
white




200
red
ca. Pant. 186c



320
light blue
ca. Pant. 2148c



300
royal blue
ca. Pant. 286c



400
green
ca. Pant. 7727c



730
grey
ca. Pant. 422c



700
black