



## FIRST STRETCHABLE POLYURETHANE TEXTILPRESSUREFOLIE WITH SUBLIMATION LAMINATION!

With patented ONYX STiX<sup>2</sup> adhesive and an activated carbon barrier layer that keeps the material stretchy and supple despite the block-out function. A short time at a low temperature protects the textile surface. Adheres to almost all types of textiles. For highly sublimating textiles, we recommend our CAD-COLOR® Sublistop!



## AVAILABLE IN

- 50 cm x 25 m roll

## RECOMMENDED FABRICS \* Test before application!

- 100% Cotton
- 100% Polyester\*
- Polyester-Cotton blends
- Lycra®- / Spandex blended
- Most nylon textiles\*

## CUTTING NOTES

Always test the cutting settings before production. Remember that the settings depend on the age of the blade used. Cutting too deep will cause difficulties when weeding or pressing.

## APPLICATION INSTRUCTIONS

Temperature: 150° C  
Time: 10 sec. Repressing: 8 sec.  
Pressure: Medium (#4-6 with Hotronix®)  
Carrier: Warm peel

## ACCESSORIES RECOMMENDED

- CAD-COLOR® MagicMask® High Tack
- Grip Cover Sheet
- Cover Sheet - Non-Sticky
- EZ Weeder®, LED Weeder, LED Pin or Tweezers
- Squeegee

## CARE INSTRUCTIONS

Washable up to 40° C. Please do not use fabric softener or bleach. Suitable for tumble drying on a gentle setting. Wash and iron inside out.

## STORAGE

Store in a cool, dry environment. Avoid direct heat or sunlight.

## DETAILS

