
CAD-CUT[®] SOFT METALLIC

SOFT METALLIC HEAT TRANSFER MATERIAL FEATURES A DISTINCT LUSTER AND SHINE

Creates a soft, metallised finish for textile decoration. It is supplied on a self-adhesive polyester carrier





AVAILABLE IN

50 cm x 25 m roll

RECOMMENDED FABRICS * Test before application!

- 100% Cotton
- 100% Polyester*
- Polyester-Cotton blends

CUTTING NOTES

Test the cut before each production run. The blade settings must be adjusted if the blade is older. For optimum cutting and weeding: Minimum line thickness of at least 1,5 mm (1/16 ").

APPLICATION INSTRUCTIONS

Temperature:	150° C
Time:	10 sec.
Pressure:	Medium (#4-6 with Hotronix®)
Carrier:	Cold peel

MULTI-COLOR DESIGNS

Press the background for 2 - 4 seconds - peel off the carrier warm / cold. Repeat this for additional colors. Press on the last color for 13 - 15 seconds. Remove the carrier cold.

ACCESSORIES RECOMMENDED

- Grip Cover Sheet
- Cover Sheet Non-Sticky
- EZ Weeder[®], LED Weeder. LED Pin or Tweezers

CARE INSTRUCTIONS

Washable up to 40° C. Please do not use fabric softener or bleach. Suitable for tumble drying on a gentle setting. Wash and iron inside out.

STORAGE

Store in a cool, dry environment. Avoid direct heat or sunlight.

DETAILS







CAD-CUT[®] SOFT METALLIC



